

FOR FLIGHT SIMULATOR USE ONLY

**BELL
B206 (BENDIX)**

NORMAL CHECKLISTS

=====
FLIGHT DECK SAFETY INSPECTION
=====

ANTI-ICE OFF
HYDRAULIC SWITCH ON
CONTROLS CHECKED
FUEL VALVE OPEN
ROTOR BRAKE OFF
CAUTION LIGHTS CB IN
BEACON OFF
INSTRUMENT LIGHTS OFF
POS LIGHTS OFF
GEN FIELD CB IN
GEN RESET CB IN
GENERATOR OFF
GYRO/ATTITUDE OFF
AVIONICS OFF
PITOT HEAT OFF

===== END OF CHECKLIST =====

=====
BEFORE START UP
=====

- BATTERY ON
- WARNING HORN MUTE
- PITCH WARNING CHECKED
- ANNUNCIATOR CHECKED
- TOT WARN LIGHT CHECKED

===== END OF CHECKLIST =====

=====
START UP
=====

AFT FUEL PUMP CB IN
FWD FUEL PUMP CB IN
BEACON ON
THROTTLE CLOSED
STARTER ENGAGE

--- N2 REACHING 15% ---

THROTTLE OPEN, IDLE
OIL TEMP MONITOR
EGT MONITOR

--- ENG OUT EXTINGUISHES ---

STARTER RELEASE

--- NR REACHING 60% ---

THROTTLE OPEN, UNTIL NR 70%

--- NR REACHING 70% ---

--- NR REACHING 70% ---

GENERATOR ON
THROTTLE CLOSE, IDLE

--- NR REACHING APROX 60% ---

AVIONICS ON
PITOT HEAT AS REQD
ANTI-ICE AS REQD
OIL TEMP STABILIZED
POS LIGHTS ON
THROTTLE OPEN, SLOWLY TO 100%

--- NR REACHING 100% ---

GYRO/ATTITUDE ON
INSTRUMENTS CHECKED

===== END OF CHECKLIST =====

=====
SHUTDOWN
=====

- THROTTLE CLOSE, IDLE
- ANTI-ICE OFF
- TEMPERATURES STABILIZED
- THROTTLE CLOSED
- FUEL VALVE OFF
- GENERATOR OFF
- AVIONICS OFF
- PITOT HEAT OFF
- GYRO/ATTITUDE OFF
- POS LIGHTS OFF
- AFT FUEL PUMP CB OUT
- FWD FUEL PUMP CB OUT
- HYDRAULICS OFF
- BEACON OFF
- BATTERY OFF

===== END OF CHECKLIST =====